



US009636022B2

(12) **United States Patent**
Nanaumi

(10) **Patent No.:** **US 9,636,022 B2**
(45) **Date of Patent:** **May 2, 2017**

(54) **SUBJECT INFORMATION ACQUISITION
DEVICE, METHOD FOR CONTROLLING
SUBJECT INFORMATION ACQUISITION
DEVICE, AND STORAGE MEDIUM
STORING PROGRAM THEREFOR**

(71) Applicant: **CANON KABUSHIKI KAISHA,**
Tokyo (JP)

(72) Inventor: **Ryuichi Nanaumi,** Kyoto (JP)

(73) Assignee: **Canon Kabushiki Kaisha,** Tokyo (JP)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 75 days.

(21) Appl. No.: **14/092,017**

(22) Filed: **Nov. 27, 2013**

(65) **Prior Publication Data**

US 2014/0155727 A1 Jun. 5, 2014

(30) **Foreign Application Priority Data**

Dec. 4, 2012 (JP) 2012-265322

(51) **Int. Cl.**

A61B 5/00 (2006.01)

A61B 8/00 (2006.01)

A61B 8/08 (2006.01)

(52) **U.S. Cl.**

CPC **A61B 5/0095** (2013.01); **A61B 8/4209**
(2013.01); **A61B 8/5207** (2013.01);
(Continued)

(58) **Field of Classification Search**

CPC ... **A61B 5/0095**; **A61B 5/7239**; **A61B 8/0825**;
A61B 8/4209; **A61B 8/485**; **A61B 8/5207**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,345,939 A 9/1994 Engeler et al.

5,640,959 A 6/1997 Hara et al.

(Continued)

FOREIGN PATENT DOCUMENTS

CN 101199430 A 6/2008

CN 102068275 A 5/2011

(Continued)

OTHER PUBLICATIONS

Lamela, et al., "Reconstruction algorithms for optoacoustic imaging based on fiber optic detectors", Independent Component Analyses, Wavelets, Neural Networks, Biosystems, and Nanoengineering IX, SPIE, Bellingham, WA, USA, vol. 8058, No. 1, May 13, 2011 (May 13, 2011), pp. 1-7, XP060017074.

(Continued)

Primary Examiner — Michael Rozanski

(74) *Attorney, Agent, or Firm* — Canon U.S.A., Inc., IP
Division

(57)

ABSTRACT

A subject information acquisition device includes an elastic wave receiving unit configured to receive elastic waves generated inside a subject and output a reception signal; and a signal processing unit configured to acquire subject information in an interest region of the subject, on the basis of the reception signal. In measurement states, the elastic wave receiving unit receives elastic waves and outputs reception signals corresponding to the measurement states. The signal processing unit corrects the reception signals by weighting factors based on measurement parameters in the measurement states, and acquires corrected reception signals in the interest region corresponding to the measurement states. The signal processing unit acquires the subject information in the interest region, on the basis of the sum of the corrected reception signals and the sum of the weighting factors.

18 Claims, 7 Drawing Sheets

